



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4183-20B	183mm	RGB HIGH OUTPUT WHITE 5600° KELVIN	900 @ 0°C	365	5 ± 1	15,000±10%	20,000
BF4220-20B	220mm		1,000 @ 0°C	405	5 ± 1	15,000±10%	20,000
BF4418-20B	418mm		1,400 @ 0°C	765	5 ± 1	15,000±10%	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION							
		DRAWN BY L. WENGSTROM		APPVD BY DATE J.K. 9/17/02		SIZE A		FSCM NO. 55335		DRAWING NO. BF 4-20B	
RELEASED TO CAD 9/17/02			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE		RELEASED DATE 9/17/02		REVISION DATE	
REV. NO.	DESCRIPTION/ECO NUMBER		APPVD DATE		SHEET 1 OF 1		REV. NO.		SHEET		